



## SAHM 240E / 240XE

### Market segments:

- Flat, fibrillated and folded tapes, single and bundled monofilaments

### Applications:

- Carpet backing, artificial grass, geotextiles, filters, sun shade fabrics

### Features / Options:

- Pneumatically operated mandrel
- Doff signal for each winding head
- Single- or double-sided frame construction

### Technology:

	240E	240XE
Material:	Flat, fibrillated and folded tape	Monofilaments, flat, fibrillated and folded tapes
Material width:	Tapes: 1 end from 0,9 to 7 mm 2 ends from 2 x 0,9 mm	Tapes: 1 end from 0,9 to 7 mm 2 ends from 2 x 0,9 mm  Monofilaments, single ends: Ø 0,15 to 0,60 mm
Drive:	Frequency-controlled	Frequency-controlled
Frame:	3- or 4-tier	3- or 4-tier
Winding ratio:	Mechanical	Electronic
Titer:	Tapes: 250 to 3500 dtex (fibrillated up to 15000 dtex)	Tapes: 250 to 3500 dtex (fibrillated up to 15000 dtex)  Monofilaments, bundled: entire titer up to 10000 dtex
Maximum winding speed:	420 m/min	420 m/min
Traverse length:	200, 250 or 300 mm	200, 250 or 300 mm
Maximum package diameter:	320 mm	320 mm
Tube inside diameter:	82,5 or 90 mm	82,5 or 90 mm
Tube length:	230, 290 or 330 mm	230, 290 or 330 mm

Combination of all maximum values is not possible.



**WINDERS + SYSTEMS**  
a member of Starlinger Group

Georg Sahn GmbH & Co. KG · Sudetenlandstrasse 33 · 37269 Eschwege · Germany

Tel.: +49 5651 804-0 · Fax: +49 5651 13620 · Internet: [www.sahmwinder.de](http://www.sahmwinder.de) · E-mail: [info@sahmwinder.de](mailto:info@sahmwinder.de)